

**RESPONSE OF METRO TUNNELS TO NEARBY
BASEMENT EXCAVATION AND BUILDING
CONSTRUCTION: INSIGHTS FROM PHYSICAL AND
NUMERICAL MODELLING**

VINAY KUMAR SINGH



**DEPARTMENT OF CIVIL ENGINEERING
INDIAN INSTITUTE OF TECHNOLOGY DELHI
FEBRUARY 2026**

© Indian Institute of Technology Delhi (IITD), New Delhi, 2026

**RESPONSE OF METRO TUNNELS TO NEARBY BASEMENT
EXCAVATION AND BUILDING CONSTRUCTION: INSIGHTS
FROM PHYSICAL AND NUMERICAL MODELLING**

by

VINAY KUMAR SINGH

Department of Civil Engineering

Submitted

in fulfillment of the requirements of the degree of Doctor of Philosophy

to the



INDIAN INSTITUTE OF TECHNOLOGY DELHI

FEBRUARY 2026

Dedicated to My Grandparents

CERTIFICATE

This is to certify that the thesis entitled "**RESPONSE OF METRO TUNNELS TO NEARBY BASEMENT EXCAVATION AND BUILDING CONSTRUCTION: INSIGHTS FROM PHYSICAL AND NUMERICAL MODELLING**" submitted by **MR. VINAY KUMAR SINGH** to the Indian Institute of Technology Delhi, is a record of the bonafide research work carried out by him under my supervision and guidance. This thesis work, in our opinion, has reached the standard, fulfilling the requirements for a **DOCTOR OF PHILOSOPHY** degree. The research report and the results presented in this thesis have not been submitted, in part or in full, to any other university or institute, for the award of any degree or diploma.

(Dr. R. Ayothiraman)

Professor
Department of Civil Engineering
IIT Delhi, New Delhi-16, India

Place: IIT Delhi

Date: 26th February 2026

ACKNOWLEDGEMENTS

The successful completion of this doctoral dissertation would not have been possible without the support, guidance, and encouragement of numerous individuals. I extend my deepest gratitude to all those who stood by me throughout this journey.

First and foremost, I am grateful to my supervisor, **Prof. R. Ayothiraman**, Department of Civil Engineering, for his unwavering support, insightful guidance, and encouragement throughout my research. His expertise, positive attitude, and constant availability despite his demanding schedule have helped me in carrying out this research. I consider it a privilege and a great honor to have pursued my Ph.D. under his guidance. His inspiring words and constructive feedback have been invaluable at every stage of this journey.

I sincerely acknowledge the valuable insights and suggestions provided by the members of my Student Research Committee (SRC): **Prof. Alok Madan (Chairman)**, **Prof. Bappaditya Manna (Subject Expert)**, and **Prof. Maloy K. Singha (External Expert)**. Their critical feedback and recommendations at various stages significantly enhanced the quality of this dissertation.

My sincere thanks go to **Prof. Vasant Matsagar**, Head of the Civil Engineering Department, IIT Delhi, for facilitating the resources and support essential for the smooth progression of my research work.

I gratefully acknowledge all the faculty members of the Department of Civil Engineering, IIT Delhi, who contributed to my academic development during coursework and beyond. A special thank you to the professors of geotechnical engineering, **Prof. G. V. Ramana**, **Prof. Manoj Datta**, **Prof. J. T. Sahoo**, **Prof. Bappaditya Manna**, and **Prof. Deepanshu Shirole** for the knowledge and perspectives they shared, which enriched my understanding and research capabilities.

I would like to thank the technical staff of the Geotechnical Engineering Laboratory and Rock Mechanics Laboratory, especially **Mr. Manoj Kumar Neelam**, **Mr. Dinesh Kumar**, **Mr. Alok**, **Mr. Lokendra**, **Mr. Ramjanam**, **Mr. Manish**, and **Mr. Suraj**, for their generous assistance throughout the experimental phases of my research. A special word of thanks goes to **Mr. Siraj Ji**, whose help in procuring materials was crucial, and to **Mr.**

Amit Bundela for his support in ensuring uninterrupted access to computational lab facilities.

I am deeply indebted to **Dr. Deepesh Bansal, Dr. Debprakash, Dr. Ashwinth Raj, Dr. Chinju Vijayan, Dr. Mayuresh,** and **Dr. Upendra** for their technical advice, moral support, and companionship throughout this Ph.D. journey. Their consistent encouragement helped me overcome several challenges.

I also acknowledge **Prof. Raghvendra Sahu** and **Dr. Sumeet Mahajan** for their guidance and support during the initial stages of my research work.

To my friends and peers, both within and outside, IIT Delhi: **Dr. Biruk, Dr. Befkadu, Dr. Saurabh, Dr. Deepak, Dr. Akshansh, Dr. Bil, Dr. Avinash, Dr. Debtanu, Dr. Sujata, Dr. Harshal, Dr. Debi, Dr. Sarangi, Dr. Abitha, Dr. Kausik,** and many others, I extend heartfelt thanks for their moral support and camaraderie throughout this journey.

Words fall short in expressing my immense gratitude to my parents: **Mr. Kanhaiya Lal Singh, Mrs. Shashi Kala Singh, Dr. Gauri Antherjanam,** and **Dr. Evasudevan Nampothiri**, whose unconditional love, sacrifices, and unwavering belief in me have been my motivation. I am also thankful to my grandparents and extended family, whose constant encouragement and blessings have guided me through every stage of life. My heartfelt thanks to my brother, **Dr. Vipul Kumar Singh**, for his consistent support and motivation, which have been invaluable throughout this journey.

Above all, I owe my deepest thanks to my beloved wife, **Dr. Akhila V**, for her unwavering love, patience, and encouragement. Her faith in me and her emotional support were my strength through the highs and lows of this Ph.D. journey. I am truly blessed to have her by my side.

Above all, I owe it all to Almighty God for granting me the wisdom, health, and strength to undertake this research task and enabling me to complete it.

Date: 26th February 2026

Vinay Kumar Singh

ABSTRACT

Over the past few years, urbanization has grown rapidly due to factors such as population increase, economic progress, and advancements in technology. This trend has led to a significant migration of people from rural regions to urban centers, seeking improved job opportunities, education, healthcare, and quality of life. For any city's growth, a good transportation system and better land use patterns play a vital role in sustainable development. Among the various sustainable transport options in cities, underground metro systems are considered effective, as they help reduce surface-level traffic congestion and free up valuable land above ground for other developments. However, constructing underground tunnels requires careful attention to the safety of nearby existing structures. To address this, many analytical, semi-analytical, and numerical approaches, along with field monitoring, to assess and manage potential risks are available. As urban development increases the space around metro corridors, it becomes a prime area for new developments. Currently, many buildings are being constructed near metro lines, such as residential complexes and commercial centers, which include basement levels, primarily intended for parking facilities, canteens, and storage facilities. Therefore, it is critical to evaluate how these new constructions impact the existing tunnels. In the past, reports have also been available where tunnel damage is reported due to these types of new developments (mainly basement excavation) in the surrounding area of the tunnel. The aim of the present research study is to investigate the effect of basement excavation and structural loading on the existing tunnels using a comprehensive experimental and numerical method.

The study includes characterization of soils, model experiments, and three-dimensional finite element analysis. The different lab tests are conducted to find the material properties of the soil, which include triaxial tests for finding the engineering properties. A total of 20 model tests, which include 12 model tests in cohesionless soil

(Yamuna sand) and 8 model tests in cohesive soil (Kaolinite clay) were conducted considering parametric variations of the number of basements, shear strength of the cohesive soil, groundwater table level, number of floors, and the horizontal offset distance from the tunnel. An experimental model setup, which includes a test tank and a hydraulically controlled tunnel excavation system, sheet pile wall, and a raft-integrated retaining wall, was fabricated for the model tests. HDPE pipe was selected to represent the tunnel lining. Strain gauges were used to assess the impact of the new construction on the existing tunnel in the model experiments. Strain gauges were fixed in both the longitudinal and lateral direction at the Crown, Invert, and Spring Levels on the tunnel lining to measure the changes. The results obtained from model tests were used to validate the numerical modelling. Numerical analysis was also validated through existing field and lab test data available in the literature, and it was found that the numerical results are in good agreement. After the validation of the numerical model in PLAXIS, an extensive parametric study was carried out for both types of soil. The soil, tunnel lining, basement excavation, and foundation were modeled using an optimized mesh density. To reduce boundary effects, a sensitivity analysis was conducted, which helped in the determination of the final model dimensions. Soil was modelled as the hardening soil model. Parametric studies were performed by examining several key factors, including the cover, the horizontal distance between the tunnel, the size of the foundation, the number of basements, the location of the groundwater table, and the different strength values in the case of clay. A total of 288 finite element analyses were carried out, including all the parametric variations.

It is found from the results that the construction of basement excavation and structural loading has a significant effect on the existing urban metro tunnels. The impact of the presence of the water table was found to increase tunnel displacement by 10 to 20% when located at the surface compared to the invert level. Cover depth between the ground

surface and the tunnel significantly affects deformation, as the effective distance between the tunnel and the foundation area is affected by the cover, and the deformation is found to increase by over 20%. The number of basement levels also had a significant impact, particularly when located closer to the tunnel ($X/D = 0.5$). In clayey soils, increasing shear strength from 20 to 30 kPa reduced displacement by more than 30%, though displacements still exceeded acceptable limits. Displacement was reduced significantly when the foundation was placed farther away ($X/D = 3.0$). The induced strain in the tunnel lining, both during excavation and the loading stage, is found to exceed 150 micro-strains (ACI, 2001) in many cases, which may eventually lead to the cracking of the tunnel lining. The displacement values exceed the limit specified by different regulating agencies (15 and 20 mm). This relative displacement may lead to spalling of the joints of the tunnel segments. The effect is observed to completely diminish beyond 12 times the dimension of the tunnel (Diameter) along the length of the tunnel and laterally, and was identified as safe for distances greater than 2.5 times the tunnel diameter. At last, it was observed that all the parametric variations have a significant impact on the existing tunnel due to the nearby new construction activities.

सार

पिछले कुछ वर्षों में शहरीकरण जनसंख्या वृद्धि, आर्थिक प्रगति और प्रौद्योगिकी में उन्नति जैसे कारकों के कारण तीव्र गति से बढ़ा है। इस प्रवृत्ति के परिणामस्वरूप बेहतर रोजगार अवसरों, शिक्षा, स्वास्थ्य सेवाओं और जीवन गुणवत्ता की तलाश में ग्रामीण क्षेत्रों से शहरी केंद्रों की ओर बड़े पैमाने पर जनसंख्या का पलायन हुआ है। किसी भी शहर के विकास के लिए एक सुदृढ़ ट्रांसपोर्टेशन सिस्टम और बेहतर लैंड यूज़ पैटर्न्स सतत विकास में महत्वपूर्ण भूमिका निभाते हैं। शहरी क्षेत्रों में उपलब्ध विभिन्न सस्टेनेबल ट्रांसपोर्ट विकल्पों में अंडरग्राउंड मेट्रो सिस्टम्स को प्रभावी माना जाता है, क्योंकि ये सतह स्तर पर ट्रैफिक कंजेशन को कम करने में सहायता करते हैं और भूमि के ऊपर के मूल्यवान क्षेत्र को अन्य विकास कार्यों के लिए मुक्त करते हैं।

हालाँकि, अंडरग्राउंड टनल्स के निर्माण में आसपास की मौजूदा संरचनाओं की सुरक्षा पर विशेष ध्यान देना आवश्यक है। इस उद्देश्य से संभावित जोखिमों का आकलन और प्रबंधन करने के लिए अनेक एनालिटिकल, सेमी-एनालिटिकल तथा न्यूमेरिकल अप्रोचेज, के साथ-साथ फील्ड मॉनिटरिंग तकनीकों का उपयोग किया जाता है। जैसे-जैसे शहरी विकास मेट्रो कॉरिडोर के आसपास बढ़ता है, यह क्षेत्र नए निर्माण कार्यों के लिए प्रमुख स्थान बन जाता है। वर्तमान में मेट्रो लाइन्स के निकट कई भवनों का निर्माण किया जा रहा है, जैसे रेजिडेंशियल कॉम्प्लेक्स और कमर्शियल सेंटर्स, जिनमें बेसमेंट लेवल्स प्रायः पार्किंग फैसिलिटीज, कैंटीन्स और स्टोरेज फैसिलिटीज के लिए बनाए जाते हैं। अतः यह अत्यंत आवश्यक है कि इन नए निर्माण कार्यों का मौजूदा टनल्स पर प्रभाव का मूल्यांकन किया जाए। अतीत में ऐसे कई रिपोर्ट उपलब्ध हैं जिनमें बेसमेंट एक्सकेवेशन जैसे नए विकास कार्यों के कारण टनल्स को क्षति होने की घटनाएँ दर्ज की गई हैं।

वर्तमान अनुसंधान अध्ययन का उद्देश्य बेसमेंट एक्सकेवेशन और स्ट्रक्चरल लोडिंग के मौजूदा टनल्स पर प्रभाव की जांच एक व्यापक एक्सपेरिमेंटल और न्यूमेरिकल पद्धति के माध्यम से करना है। इस अध्ययन में साँइल कैरेक्तराइजेशन, मॉडल एक्सपेरिमेंट्स और थ्री-डायमेंशनल फाइनाइट एलीमेंट

एनालिसिस सम्मिलित हैं। विभिन्न लेबोरेटरी टेस्ट्स द्वारा साँइल के मटेरियल प्रॉपर्टीज निर्धारित किए गए, जिनमें इंजीनियरिंग प्रॉपर्टीज प्राप्त करने हेतु ट्राइएक्सियल टेस्ट्स शामिल हैं। कुल 20 मॉडल टेस्ट्स संचालित किए गए, जिनमें 12 मॉडल टेस्ट्स कोहेसिव साँइल (यमुना सैंड) में और 8 मॉडल टेस्ट्स कोहेसिव साँइल (काओलिनाइट क्ले) में किए गए। इन परीक्षणों में नंबर ऑफ बेसमेंट्स, कोहेसिव साँइल की शियर स्ट्रेंथ, ग्राउंडवॉटर टेबल लेवल, नंबर ऑफ फ्लोर्स तथा टनल से हॉरिजॉन्टल ऑफसेट डिस्टेंस जैसे पैरामेट्रिक वेरिएशन्स पर विचार किया गया।

मॉडल टेस्ट्स के लिए एक एक्सपेरिमेंटल मॉडल सेटअप तैयार किया गया, जिसमें टेस्ट टैंक, हाइड्रॉलिकली कंट्रोल्ड टनल एक्सकेवेशन सिस्टम, शीट पाइल वॉल तथा राफ्ट-इंटीग्रेटेड रिटेनिंग वॉल शामिल थे। टनल लाइनिंग का प्रतिनिधित्व करने के लिए एचडीपीई पाइप का चयन किया गया। मॉडल एक्सपेरिमेंट्स में नए निर्माण के प्रभाव का आकलन करने के लिए स्ट्रेन गेजस का उपयोग किया गया। स्ट्रेन गेजस को टनल लाइनिंग के क्राउन, इनवर्ट और स्प्रिंग लेवल्स पर लॉन्गिट्यूडिनल तथा लेटरल दिशाओं में स्थापित किया गया ताकि परिवर्तनों को मापा जा सके।

मॉडल टेस्ट्स से प्राप्त परिणामों का उपयोग न्यूमेरिकल मॉडलिंग को वैलिडेट करने के लिए किया गया। न्यूमेरिकल एनालिसिस को साहित्य में उपलब्ध फील्ड तथा लेबोरेटरी डेटा के माध्यम से भी वैलिडेट किया गया, और पाया गया कि न्यूमेरिकल रिजल्ट्स अच्छे सामंजस्य में हैं। प्लैक्सिस में न्यूमेरिकल मॉडल के वैलिडेशन के पश्चात, दोनों प्रकार की साँइल के लिए एक विस्तृत पैरामेट्रिक स्टडी की गई। साँइल, टनल लाइनिंग, बेसमेंट एक्सकेवेशन और फाउंडेशन को ऑप्टिमाइज्ड मेश डेंसिटी के साथ मॉडल किया गया। बाउंडरी इफेक्ट्स को कम करने हेतु सेंसिटिविटी एनालिसिस किया गया, जिससे अंतिम मॉडल डायमेंशन्स निर्धारित किए गए। साँइल को हार्डनिंग साँइल मॉडल के रूप में मॉडल किया गया।

पैरामेट्रिक स्टडीज़ में कवर, टनल और फाउंडेशन के बीच हॉरिजॉन्टल डिस्टेंस, फाउंडेशन का साइज़, नंबर ऑफ बेसमेंट्स, ग्राउंडवॉटर टेबल की स्थिति तथा क्ले के मामले में विभिन्न स्ट्रेंथ वैल्यूज़

जैसे प्रमुख कारकों का अध्ययन किया गया। सभी पैरामेट्रिक वेरिएशन्स को सम्मिलित करते हुए कुल 288 फाइनाइट एलीमेंट एनालिसिस किए गए।

परिणामों से पाया गया कि बेसमेंट एक्सकेवेशन और स्ट्रक्चरल लोडिंग का मौजूदा अर्बन मेट्रो टनल्स पर महत्वपूर्ण प्रभाव पड़ता है। वॉटर टेबल की उपस्थिति से टनल डिस्प्लेसमेंट में 10 से 20% तक वृद्धि पाई गई जब यह इनवर्ट लेवल की तुलना में सरफेस पर स्थित था। ग्राउंड सरफेस और टनल के बीच कवर डेपथ डिफॉर्मेशन को महत्वपूर्ण रूप से प्रभावित करता है, और डिफॉर्मेशन में 20% से अधिक वृद्धि देखी गई। नंबर ऑफ बेसमेंट लेवल्स का भी महत्वपूर्ण प्रभाव पाया गया, विशेष रूप से जब यह टनल के निकट ($X/D = 0.5$) स्थित था।

क्लेयी सॉइल्स में शियर स्ट्रेंथ को 20 kPa से 30 kPa तक बढ़ाने पर डिस्प्लेसमेंट में 30% से अधिक की कमी पाई गई, हालांकि डिस्प्लेसमेंट स्वीकार्य सीमाओं से अधिक ही रहा। फाउंडेशन को टनल से अधिक दूरी ($X/D = 3.0$) पर रखने से डिस्प्लेसमेंट में उल्लेखनीय कमी देखी गई। एक्सकेवेशन तथा लोडिंग स्टेज के दौरान टनल लाइनिंग में उत्पन्न स्ट्रेन कई मामलों में 150 माइक्रोस्ट्रेन्स (ACI, 2001) से अधिक पाया गया, जिससे अंततः टनल लाइनिंग में क्रैकिंग की संभावना उत्पन्न हो सकती है। डिस्प्लेसमेंट वैल्यूज़ विभिन्न रेगुलेटिंग एजेंसीज़ द्वारा निर्दिष्ट सीमा (15 तथा 20 mm) से अधिक पाए गए। यह रिलेटिव डिस्प्लेसमेंट टनल सेगमेंट्स के जॉइंट्स में स्पॉलिंग का कारण बन सकता है।

यह प्रभाव टनल की लंबाई तथा पार्श्व दिशा में टनल डायमीटर के 12 गुना से अधिक दूरी पर पूर्णतः समाप्त होता पाया गया, और टनल डायमीटर के 2.5 गुना से अधिक दूरी को सुरक्षित माना गया। अंततः यह निष्कर्ष निकाला गया कि सभी पैरामेट्रिक वेरिएशन्स निकटवर्ती नए निर्माण कार्यों के कारण मौजूदा टनल्स पर महत्वपूर्ण प्रभाव डालते हैं।

TABLE OF CONTENTS

CERTIFICATE	i
ACKNOWLEDGEMENTS	iii
ABSTRACT	v
TABLE OF CONTENTS	xiii
LIST OF FIGURES	xix
LIST OF TABLES	xxvii
LIST OF NOTATIONS	xxix
CHAPTER 1 INTRODUCTION	1
1.1 Introduction	1
1.2 History of the Metro System and its Advantages	2
1.3 Problems Associated with Urban Tunnelling	5
1.4 Need for the Present Study	7
1.5 Research Objectives	9
1.6 Organization of the thesis	10
CHAPTER 2 REVIEW OF LITERATURE	13
2.1 Introduction	13
2.2 Effects of Tunneling on Nearby Foundations/Structures	15
2.3 Effects of New Construction Activities on Tunnels	31
2.4 Critical Assessment of Literature	56
2.5 Summary	56

CHAPTER 3	PHYSICAL MODELLING OF TUNNEL-BASEMENT-BUILDING INTERACTION	57
3.1	Introduction	57
3.2	Materials Characterization	57
3.2.1	Soil	58
3.2.2	HDPE	62
3.2.3	Steel	63
3.3	Scaling Laws for Physical Modeling	63
3.4	Experimental Setup	65
3.4.1	Tunnel	65
3.4.2	Test tank	67
3.4.3	Raft-integrated retaining wall	70
3.4.4	Temporary sheet pile	71
3.4.5	Tunnel excavator	72
3.4.6	Compaction equipment	74
3.4.7	Sensors and Data Acquisition System	74
3.5	Model Test Procedure	76
3.5.1	Soil bed preparation	77
3.5.2	Tunnel excavation	82
3.5.3	Basement excavation	82
3.5.4	Raft-retaining wall installation	83
3.5.5	Superstructure loading	83
3.6	Test program	83

3.7	Summary	84
CHAPTER 4	RESULTS AND DISCUSSION OF MODEL EXPERIMENTS	87
4.1	Introduction	87
4.2	Results and Discussion of Experiments in Sand	88
4.3	Results and Discussion of experiments in clay	97
4.4	Summary	105
CHAPTER 5	VALIDATION FOR FINITE ELEMENT ANALYSIS	107
5.1	Introduction	107
5.2	Introduction to PLAXIS 3D	107
5.2.1	Important features of PLAXIS 3D	109
5.2.2	Material Models in PLAXIS 3D	109
5.2.3	Meshing, boundary conditions, and calculation phases	113
5.2.4	Analysis steps	115
5.3	Validation through Existing Literature	116
5.3.1	Surface settlement trough due to tunnelling	116
5.3.2	Pile foundation response to tunnelling	119
5.3.3	Comparison with the Centrifuge test of Ong et al. (2007)	120
5.4	Validation using the Present Experimental Data	122
5.4.1	Validation with experiments in sand	126
5.4.2	Validation with experiments in clay	133
5.5	Summary	142

CHAPTER 6	PARAMETRIC FEM STUDY ON TUNNEL-EXCAVATION-STRUCTURAL LOADING INTERACTION IN SAND	143
6.1	Introduction	143
6.2	Numerical Modelling	143
6.2.1	Boundary conditions	145
6.2.2	Discretization	146
6.3	Material Modelling	146
6.3.1	Soil	146
6.3.2	Tunnel	147
6.3.3	Basement raft and retaining wall	148
6.3.4	Temporary sheet pile walls	148
6.4	Simulation of Construction and Loading Stages	149
6.5	Parametric Study	150
6.6	Typical displacement results	150
6.6.1	Displacement contours and displacement vectors	150
6.6.2	Total displacement of the tunnel lining	156
6.7	Parametric variation results	162
6.7.1	Number of basements (Nb)	163
6.7.2	Horizontal offset distance (X/D)	168
6.7.3	Foundation size	172
6.7.4	Location of the groundwater table	177
6.7.5	Cover depth (C/D)	181

6.8	Summary	185
PARAMETRIC FEM STUDY ON TUNNEL- CHAPTER 7 EXCAVATION-STRUCTURAL LOADING INTERACTION IN CLAY		
7.1	Introduction	187
7.2	Numerical Modelling	187
7.3	Simulation of Construction and Loading Stages	188
7.4	Parametric Study	188
7.5	Results of Numerical Analysis	189
7.6	Parametric Variation Results in Clay	191
7.6.1	Number of basements (Nb)	192
7.6.2	Horizontal offset distance (X/D)	197
7.6.3	Foundation size	201
7.6.4	Shear strength of the soil	206
7.6.5	Cover depth (C/D)	210
7.7	Summary	214
CHAPTER 8 SUMMARY AND CONCLUSIONS		
8.1	Summary	217
8.2	Major Conclusions	218
8.3	Major Contributions	221
8.4	Limitations	222
8.5	Suggestions for future research	222

REFERENCES	225
LIST OF PUBLICATIONS	239
BIODATA	241

LIST OF FIGURES

Figure No.	Figure Caption	Page No.
1.1	Metro network of India	3
1.2	Year-wise growth of metro network in India	4
1.3	(a) Effect of tunnelling on the existing structure, (b) Effect of excavation near the existing tunnel, and (c) Effect of loading on the existing tunnel.	8
2.1	Building failure due to tunneling (a) Munich in Germany, 1994; (b) Lausanne in Switzerland, 2005; (c) Taegu in South Korea, 2004; (d) Kolkata metro in India, 2019.	13
2.2	Various forms of tunneling in current practice.	14
2.3	Numerical simulation of tunnel construction (after Mroueh and Shahrour, 2002)	19
2.4	Foundation layout of Lee House and Air Rights Building with respect to 2 B.T. tunnels (after Benton and Phillips, 1991)	33
2.5	Cross-section 1-1 of Lee House and Air Rights Building with respect to 2 B.T. tunnels (after Benton and Phillips, 1991)	33
2.6	Plan view of the shape and relative position of the excavation and twin tunnel	48
3.1	Grain size distribution curve of Yamuna sand	59
3.2	Variation of Deviator Stress with Strain	60
3.3	Stress Path in Triaxial Tests for Yamuna Sand	61
3.4	Grain size distribution curve of Kaolinite Clay	62
3.5	Tunnel (HDPE pipe): (a) Schematic view, (b) 3D view, and (c) Photographic view	66
3.6	Schematic diagram of the test setup, (a) Sectional view (b) Plan view	68
3.7	Model test setup (a) Photographic view, and (b) Closeup view	69
3.8	Fabricated Raft-integrated retaining wall. (a) Schematic Plan view, (b) Schematic front view, and (c) Photographic view	70

3.9	Line diagram of sheet pile wall	71
3.10	Fabricated sheet pile wall. (a) Schematic plan view, (b) Schematic front view, and (c) Photographic view	72
3.11	Fabricated tunnel excavator. (a) Schematic view, and (b) Photographic view	73
3.12	Tunnel excavation using a fabricated excavator	74
3.13	Compaction Equipment's (a) Mini plate vibrator, (b) Smooth roller, and (c) Sheep foot roller	75
3.14	Multi-channel data logger	76
3.15	Test tank with layer markings	78
3.16	Calibration of plate vibrator. (a) Relative density with respect to speed and number of passes, (b) Repeatability of test data	79
3.17	Variation of relative density with layer number for the twelve tests conducted	80
3.18	Variation of Shear strength with water content	81
3.19	The pocket shear vane test apparatus	82
4.1	Locations at which strain gauges are measured	88
4.2	Plan and section showing parametric variations in sand experiments	90
4.3	Variation of circumferential strain at different phases of the experiments in sand: (a) Crown, (b) Invert, (c) LSL, and (d) RSL at $Y/D=0$.	91
4.4	Variation of longitudinal strain at different phases of the experiments in sand: (a) Crown, (b) Invert, (c) LSL, and (d) RSL $Y/D=0$.	92
4.5	Change in the circumferential strain along the normalized tunnel length (Y/D) in the excavation phase of experiments in sand: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	93
4.6	Change in the circumferential strain along the normalized tunnel length (Y/D) in the highest loading phase of experiments in sand: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	94

4.7	Change in the longitudinal strain along the normalized tunnel length (Y/D) in the excavation phase of experiments in sand: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	95
4.8	Change in the longitudinal strain along the normalized tunnel length (Y/D) in the highest loading phase of experiments in sand: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	96
4.9	Plan and Section showing parametric variations in clay experiments	99
4.10	Variation of circumferential strain at different phases of the experiments in clay: (a) Crown, (b) Invert, (c) LSL, and (d) RSL at $Y/D=0$	100
4.11	Variation of longitudinal strain at different phases of the experiments in clay: (a) Crown, (b) Invert, (c) LSL, and (d) RSL at $Y/D=0$	101
4.12	Change in the circumferential strain along the normalized tunnel length (Y/D) in the excavation phase of the experiments in clay: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	102
4.13	Change in the circumferential strain along the normalized tunnel length (Y/D) in the loading phase of the experiments in clay: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	103
4.14	Change in the longitudinal strain along the normalized tunnel length (Y/D) in the excavation phase of the experiments in clay: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	104
4.15	Change in the longitudinal strain along the normalized tunnel length (Y/D) at the end of the loading phase of the experiments in clay: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	105
5.1	Cartesian coordinate system in PLAXIS	108
5.2	Different modulus definitions	112
5.3	10-noded tetrahedral element	114
5.4	Comparison of results with the various cases (a) Barcelona (b) Bangkok and (c) Thunderbay	118

5.5	Tunnelling near the pile foundation	120
5.6	Predicted and reported pile response due to tunneling with 1% and 5% volume loss. (a) Bending Moment and (b) Deflection	121
5.7	Variation of bending moment with depth	122
5.8	Finite element model	125
5.9	Variation of circumferential strain at different construction phases ($X/D = 0.5$, $NB = 3$, $D_w = GL$): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	128
5.10	Variation of longitudinal strain at different construction phases ($X/D = 0.5$, $NB = 3$, $D_w = GL$) along the length of the tunnel. (a) Crown, and (b) LSL measured experimentally and computed numerically.	130
5.11	Variation of circumferential strain at the center of the tunnel ($Y/D = 0$) measured experimentally and computed numerically for the twelve model tests: (a) Crown excavation phase, (b) LSL excavation phase, (c) Crown loading phase, and (d) LSL loading phase.	131
5.12	Measured and computed strain at the outer surface of the tunnel lining in sand. (a) excavation phase and (b) loading phase	134
5.13	Variation of circumferential strain at different construction phases ($X/D = 0.5$, $NB = 3$, $S_u = 20$ kPa): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	136
5.14	Variation of longitudinal strain at different construction phases ($X/D = 0.5$, $NB = 3$, $S_u = 20$ kPa) along the length of the tunnel: (a) Crown, and (b) LSL measured experimentally and computed numerically.	138
5.15	Variation of circumferential strain at the center of the tunnel ($Y/D = 0$) measured experimentally and computed numerically for the twelve model tests (a) Crown excavation phase, (b) LSL excavation phase, (c) Crown loading phase, and (d) LSL loading phase.	139

5.16	Measured and computed strain at the outer surface of the tunnel lining in clay. (a) excavation phase and (b) loading phase	141
6.1	Outline of the model and structural elements	145
6.2	Typical FE Mesh in 3D analysis	146
6.3	Typical displacement contours due to excavation and structural loading near the existing tunnel	152
6.4	Total displacement vector due to excavation and structural loading near the existing tunnel	153
6.5	Total displacement along the length of the tunnel due to excavation and structural loading near the existing tunnel	155
6.6	Deformation vector of tunnel lining due to excavation and structural loading near the existing tunnel (scaled up to 500 times)	156
6.7	Displacement of the tunnel near the new construction area due to excavation and structural loading near the existing tunnel along the length (scaled up to 500 times).	157
6.8	Total displacement along the normalized length of the tunnel (Y/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	160
6.9	Total displacement with respect to different construction stages: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	161
6.10	Total displacement comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	163
6.11	Normalized bending moment comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	164
6.12	Normalized shear force comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	165
6.13	Normalized axial force comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	166
6.14	Strain comparison with the number of basements	166
6.15	Total displacement comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	167

6.16	Normalized bending moment comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	168
6.17	Normalized shear force comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	169
6.18	Normalized axial force comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	170
6.19	Strain variation with the normalized horizontal offset distance (X/D)	171
6.20	Total displacement comparison with the different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	172
6.21	Normalized bending moment comparison with different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	173
6.22	Normalized shear force comparison with different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	174
6.23	Normalized axial force comparison with different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	175
6.24	Strain comparison with different sizes of the foundation	175
6.25	Total displacement comparison with different locations of the groundwater table: (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	176
6.26	Normalized bending moment comparison with different locations of the groundwater table: (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	177
6.27	Normalized shear force comparison with different locations of the groundwater table: (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	178
6.28	Normalized axial force comparison with different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	179
6.29	Strain comparison with different locations of the groundwater table	180

6.30	Total displacement comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	181
6.31	Normalized bending moment comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	182
6.32	Normalized shear force comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	182
6.33	Normalized axial force comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	183
6.34	Comparison of strain with different covers	184
7.1	Total displacement along the normalized length of the tunnel (Y/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	189
7.2	Total displacement comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	190
7.3	Normalized bending moment comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	192
7.4	Normalized shear force comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	193
7.5	Normalized axial force comparison with the number of basements: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	193
7.6	Strain comparison with the number of basements	194
7.7	Total displacement comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	195
7.8	Normalized bending moment comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	196
7.9	Normalized shear force comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	197
7.10	Normalized axial force comparison with the normalized horizontal offset distance (X/D): (a) Crown, (b) Invert, (c) LSL, and (d) RSL	198

7.11	. Strain variation with the normalized horizontal offset distance (X/D)	198
7.12	Total displacement comparison with the different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	199
7.13	Normalized bending moment comparison with different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	200
7.14	Normalized shear force comparison with different sizes of the foundation. (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	201
7.15	Normalized axial force comparison with different sizes of the foundation: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	202
7.16	Strain comparison with different sizes of the foundation	202
7.17	Total displacement comparison with different shear strength: (a) Crown, (b) Invert, (c) LSL, and (d) RSL.	203
7.18	Normalized bending moment comparison with different shear strengths: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	204
7.19	Normalized shear force comparison with different shear strengths: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	205
7.20	Normalized axial force comparison with different shear strengths: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	206
7.21	Strain comparison with different shear strengths	206
7.22	Total displacement comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	207
7.23	Normalized bending moment comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	208
7.24	Normalized shear force comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	209
7.25	Normalized axial force comparison with different covers: (a) Crown, (b) Invert, (c) LSL, and (d) RSL	210
7.26	Comparison of strain with different covers	210

LIST OF TABLES

Table No.	Table Caption	Page No.
1.1	Metro network worldwide	2
2.1	Summary of literature available on the impact of the new construction activities on the existing tunnel	49
3.1	Materials used in model tests	57
3.2	Index properties of Yamuna sand	59
3.3	Index properties of Kaolinite Clay	62
3.4	Properties of Steel and HDPE	63
3.5	Scaling laws	65
3.6	Details of test program	84
4.1	Parametric variations in sand experiments	89
4.2	Different phases in sand experiments	89
4.3	Test program in clay	97
4.4	Different phases in clay experiments	98
5.1	Material properties of different structural elements	125
5.2	Soil properties used for numerical analysis	127
5.3	Different phases simulated in the analysis of sand	128
5.4	Different phases simulated in the analysis of clay	135
6.1	Parametric variations in sand experiments	144
6.2	Boundary Conditions	145

6.3	Properties of the tunnel lining, raft, retaining wall and sheet pile	148
6.4	Properties of the tunnel strut and counterfort	149
6.5	Renumbering of construction stages for plotting purposes	150
7.1	Parametric variations in clay experiments	185
7.2	Renumbering of construction stages for plotting purposes	188

LIST OF NOTATIONS

UN	United Nations
TBM	Tunnel boring machines
NATM	New Austrian Tunnelling Method
FE	Finite Element
E	Young's modulus
μ	Poisson's ratio
IS	Indian Standards
C_u	Coefficient of uniformity
C_c	coefficient of curvature
G_s	Specific Gravity
γ	Unit weight
γ_{dmax}	Maximum dry density
γ_{dmi}	Minimum dry density
PI	Plastic index
CD	Consolidated drained
HDPE	High-density polyethylene
D_{ex}	Depth of excavation
D	Depth of penetration
RSL	Right Spring Level
LSL	Left Spring Level
D_w	Depth of the water table
GL	Ground level
IL	Invert Level
N_b	Number of basements
X	Horizontal offset distance between the edge of the raft and the center of the tunnel
D	Diameter of the tunnel
S_u	Undrained Cohesion

ACI	American Concrete Institute
ε	Strain
MC	Mohr Coulomb
HS	Hardening Soil
ϕ°	Friction angle
p^{ref}	Reference pressure
E_{50}^{ref}	Plastic straining due to primary deviatoric loading
$E_{\text{oed}}^{\text{ref}}$	Plastic straining due to primary compression
$E_{\text{ur}}^{\text{ref}}$	Elastic unloading/reloading modulus
E_{oed}	Oedometer modulus
$E_{\text{oed}}^{\text{ref}}$	Reference Oedometer modulus
E_0	Initial tangent modulus
E_{50}	Secent Modulus at 50% strength
E_{ur}	Unload-reload modulus
c_u	Undrained Cohesion
M	Bending Moment
I	Moment of Inertia
Q	Shear force
ψ°	Dilatancy angle
m	Power for stress level dependency on stiffness
R_{inter}	Interface reduction factor
R-kn	Right Knee
R-sh	Right Shoulder
L-sh	Left Shoulder
L-kn	Left knee