

**DETERMINATION OF FORMWORK STRIPPING TIME
FOR REINFORCED CEMENT CONCRETE MEMBERS AT
VARIOUS TEMPERATURES**

SIDDHARTH SHANKAR



**DEPARTMENT OF CIVIL ENGINEERING
INDIAN INSTITUTE OF TECHNOLOGY DELHI**

NOVEMBER 2024

© Indian Institute of Technology Delhi (IITD), New Delhi, 2024

**DETERMINATION OF FORMWORK STRIPPING TIME
FOR REINFORCED CEMENT CONCRETE MEMBERS AT
VARIOUS TEMPERATURES**

by

SIDDHARTH SHANKAR

Department of Civil Engineering

*Submitted in fulfillment of the requirements of the degree of
Doctor of Philosophy*

to the



INDIAN INSTITUTE OF TECHNOLOGY DELHI

NOVEMBER 2024

The thesis is dedicated to Siddharth's parents and younger brother, Rahul Shankar.

CERTIFICATE

This is to certify that the thesis entitled “**Determination of formwork stripping time for reinforced cement concrete members at various temperatures**”, being submitted by **Mr. Siddharth Shankar (Entry No. 2019CEZ8476)** to the Department of Civil Engineering, Indian Institute of Technology Delhi for the fulfillment of the requirements of the award of the degree of the Doctor of Philosophy, is a bonafide record of the research work carried out by him under our supervision and guidance. In our opinion, the thesis work has reached the requisite standard, fulfilling the requirements for the degree of Doctor of Philosophy.

The contents of this thesis, in full or in part, have not been submitted to any other University or Institute for the award of any degree or diploma.

Dr Kumar Neeraj Jha

(Professor)

Department of Civil Engineering

Indian Institute of Technology, Delhi

New Delhi – 110016

India

Dr A. K. Jain

(Retired Professor)

Department of Civil Engineering

Indian Institute of Technology, Delhi

New Delhi – 110016

India

ACKNOWLEDGEMENTS

Firstly, I would like to thank Lord Shiva for all His help and support in finishing my thesis, especially when I was down and needed His support.

I sincerely thank Professors K. N. Jha and A. K. Jain of the IIT Delhi Department of Civil Engineering for their direction and encouragement during my academic career. Their unfailing encouragement and invaluable advice have been essential to my growth. Their participation and support during the study were excellent. Working under their direction opened my eyes and was an amazing experience.

I am thankful to my student research committee members, Prof. R. Ayothiraman and Prof. A. Madan of the Department of Civil Engineering, IIT Delhi, and Prof. B. P. Patel, Department of Applied Mechanics, IIT Delhi, for providing me with their valuable input and suggestions throughout my journey of Ph.D. study.

I wish to take this opportunity to extend my sincere thanks to Prof. Vasant Matsagar for allowing me to undertake the course work in earthquake-resistant design. I am also thankful to Dr. Arnab Banerjee, and other faculty members of IIT Delhi with whom I interacted occasionally. I also thank all the Department of Civil Engineering, IIT Delhi staff members, especially Mr. Randhir Kumar Jha, Mr. Rajeev Aggarwal, Mr. Jeet Ram, and Mr. Amit Kumar, for all possible help and guidance they rendered during my research work.

I want to thank Mr. Biri Singh and all the staff of the IITD concrete laboratory of the civil engineering department for their continuous help during the experimental research work. I want to express my gratitude to all my colleagues in the research group and my senior acquaintances, with whom I have engaged in several technical conversations during the various stages of my research.

As I progress in my journey towards obtaining my Ph.D., I want to convey my gratitude to my parents and other relatives sincerely. Their steadfast backing, exemplified by individual support, and their motivation, demonstrated through specific encouragement cases, have been the foundations of my resilience throughout this journey. I am sincerely fortunate to have them in my life.

I am sincerely thankful to my parent institute (Institute of Engineering, Central Campus, Pulchowk-Tribhuvan University, Nepal) for allowing me to pursue my Ph.D. from IIT Delhi. I acknowledge the support provided by my seniors Prof. Hikmat Raj Joshi, Prof. Premnath Maskey, Prof. Tri Ratna Bajracharya, Prof. Gokarna Bahadur Motra, Prof. Kamal Bahadur Thapa, Prof. Shashidhar Ram Joshi, Dr. Bharat Mandal, Dr. Indra Prasad Acharya, Dr.Pawan Bhattarai, Prof. Durga Sangraula, and Prof. Premchandra Jha.

Lastly, I would like to express my gratitude to IIT Delhi and the Civil Engineering Department, particularly for embracing me and providing me with all the resources I required for my studies, including a library, grants, and laboratories. This place will always hold a special place in my heart since it gave me a warm heaven during my stay and an encouraging environment in which to develop my research ideas. I am sure my stay on this campus will be one of my life's most memorable periods.

Siddharth Shankar

ABSTRACT

One of the most accepted composite structural construction materials used globally to build infrastructure and shelters is reinforced cement concrete (RCC). Formwork is essential to RCC construction, ensuring concrete structures are cast precisely and accurately. Determining the duration necessary for removing formwork is a significant concern in reinforced concrete construction, as safety and cost-effectiveness rely on it. The removal of formwork should be delayed until the hardened concrete has attained adequate strength to withstand all applied stresses. The duration of removing the formwork is mostly based on the types of cement and concrete grade, as well as the ambient temperature and relative humidity. There is a scarcity of scholarly articles and other sources specifically addressing the duration required for removing formwork from RCC constructions. Furthermore, there is a dearth of studies, which investigates the impact of temperature on the duration required for formwork stripping. Hence, the author employed an experimental methodology to ascertain the duration required for removing the formwork from RCC structures under varying ambient environmental temperatures.

The study initially entailed thoroughly examining the provisions in the codes of India, Britain, the United States, Japan, Germany, and Uganda concerning the duration required for formwork to be removed. It has been observed that there is a lack of consistency among countries regarding formwork stripping time. Certain codes depend on attaining a minimum level of strength, while others rely on establishing the minimum duration for stripping, and some codes describe both criteria. The results of my study indicate that most codal provisions do not provide specific guidelines about stripping time when the temperature is below 15°C.

Certain codes recommend field testing and non-destructive tests (NDTs) to ascertain the duration required for stripping, especially when there are deviations from the parameters indicated in the standards. Typically, for structural elements that bend, it is advisable to remove the bottom formwork once the freshly poured concrete reaches a compressive strength that is 70% or greater than the intended strength. The duration for removing the formwork of various concrete components, as outlined in the codes of practice adhered to in different nations, ranges from twelve hours to twenty-eight days. Nevertheless, certain regulations have specified the duration for removing formwork based on the compressive strength of the concrete in place, ranging from 3.5 MPa to 14 MPa (N/mm²).

Based on the experiments conducted by the author, removing the formwork for vertical concrete structures within a time frame ranging from 6 hours to 5.5 days is necessary. The specific duration depends on the type of cement used and the temperature range, which can vary from 0°C to 45°C. The duration for removing horizontal formwork varies from 2.6 to 124.4 days, depending on the cement grade and the ambient temperature range of 45°C to 0°C. It is important to use caution when removing the formwork to avoid excessive stress and potential damage to the concrete, particularly when the surrounding temperature is below 15°C. This is due to the lack of guidance in many standard codes of practice regarding the appropriate period for stripping when the temperature is below 15°C. Based on the laboratory findings from this study conducted at IIT Delhi, it is recommended that nominal mix cement concrete should possess a compressive strength exceeding 3.50 MPa to safely remove the vertical formwork in concrete made with ordinary Portland cement (OPC). For concrete made using Portland Pozzolana Cement (PPC), the compressive strength should be at least 3.25 MPa.

Nevertheless, variations in material properties, environmental circumstances, and construction techniques might influence the time of the stripping process. This study investigates non-destructive testing techniques to ascertain the optimal timing for removing formwork without causing harm to the concrete structure. This research utilizes rebound hammer and ultrasonic pulse velocity (UPV) measurements technique. In the case of flexural members, the bottom formwork should not be removed until the hardened concrete reaches a compressive strength of at least 70 percent. A minimum strength of 3.5 MPa is required for vertical concrete elements to prevent spalling of concrete. Based on these criteria, this study suggests that the formwork should be removed when the rebound number (RN) exceeds 3.0 units and the ultrasonic pulse velocity (UPV) is greater than 2.6 km/s for vertical components. For flexural concrete elements, it is advised that the RN and UPV values exceed 15.0 units and 3.0 km/s, respectively. The proposed technique offers a more reliable and accurate way of evaluating the time at which formwork can be removed, considering different atmospheric conditions and variable compositions of concrete.

The optimal efficiency in RCC construction is attained by removing the formwork as soon as feasible while ensuring that there is no damage caused to the concrete. This study aims to assess the efficacy of superplasticizers and nanomaterials in the fresh concrete mixture for decreasing the time required to remove the formwork from reinforced concrete structures in cold ambient temperatures (below 15°C). According to the experimental investigation, 0.5% superplasticizers combined with 1% Nano-colloidal silica (NCS) can effectively reduce the time required for stripping, resulting in lower formwork expenses. This effect remains even when the ambient temperature falls below 15°C. Vertical formwork significantly reduces the time needed for formwork stripping, decreasing it from 4.5 days to just one day within the 0-5°C temperature range. However, the time required to remove the slab formwork is reduced from 54 to 37 days at 0°C. The cost analysis

demonstrates that by incorporating 0.5% superplasticizers and 1% NCS into the concrete, the total cost of RCC can be decreased due to the reduction of formwork expenses. This study presents the initial results of experiments carried out in a concrete laboratory to ascertain the compressive strength and extraction time for formwork removal from vertical and horizontal concrete elements using Destructive and Non-Destructive Tests.

The research determines the formwork stripping time for members made of reinforced cement concrete at different temperatures. This information can be used by practitioners in the RCC works carried out at different temperatures, more so when the temperature is below 15°C.

Keywords: Admixtures, Ambient temperature, Cement, Concrete, Cost analysis, Destructive tests (DT), Horizontal and vertical formwork, Maturity of concrete, Nanomaterials, Non-destructive tests (NDT), Rebound hammer (RH), Stripping period, Superplasticizers, Ultrasonic pulse velocity (UPV).

सारांश

दुनिया भर में अवसंरचना और आश्रयों का निर्माण करने के लिए प्रयुक्त सबसे स्वीकृत समय संरचनात्मक निर्माण सामग्री में से एक प्रबलित सीमेंट कंक्रीट (आरसीसी) है। फार्मवर्क आरसीसी निर्माण में आवश्यक है, यह सुनिश्चित करते हुए कि कंक्रीट संरचनाओं को सटीक और सही ढंग से ढाला गया है। फार्मवर्क हटाने के लिए आवश्यक समय निर्धारण प्रबलित कंक्रीट निर्माण में एक महत्वपूर्ण चिंता का विषय है, क्योंकि सुरक्षा और लागत-प्रभावशीलता इस पर निर्भर करती है। फार्मवर्क को तब तक नहीं हटाया जाना चाहिए जब तक कि कठोर कंक्रीट पर्याप्त शक्ति प्राप्त नहीं कर लेता है ताकि सभी लागू तनावों को सहन किया जा सके। फार्मवर्क हटाने की अवधि मुख्य रूप से सीमेंट के प्रकार और कंक्रीट ग्रेड, साथ ही परिवेश के तापमान और सापेक्ष आर्द्रता पर आधारित होती है। आरसीसी निर्माण से फार्मवर्क हटाने के लिए आवश्यक अवधि पर विशेष रूप से चर्चा करने वाले विद्वतापूर्ण लेखों और अन्य स्रोतों की कमी है। इसके अलावा, तापमान का फार्मवर्क स्ट्रिपिंग की अवधि पर प्रभाव का अध्ययन करने वाले अध्ययनों की भी कमी है। इसलिए, लेखक ने परिवेश के विभिन्न तापमानों के तहत आरसीसी संरचनाओं से फार्मवर्क हटाने के लिए आवश्यक अवधि का पता लगाने के लिए एक प्रयोगात्मक पद्धति का उपयोग किया।

अध्ययन में प्रारंभ में भारत, ब्रिटेन, संयुक्त राज्य, जापान, जर्मनी, और युगांडा के कोड में फार्मवर्क हटाने की अवधि के संबंध में प्रावधानों का गहन परीक्षण शामिल था। यह देखा गया है कि फार्मवर्क स्ट्रिपिंग समय के संबंध में देशों के बीच असंगति की कमी है। कुछ कोड न्यूनतम स्तर की शक्ति प्राप्त करने पर निर्भर करते हैं, जबकि अन्य न्यूनतम स्ट्रिपिंग अवधि स्थापित करने पर निर्भर करते हैं, और कुछ कोड दोनों मानदंडों का वर्णन करते हैं। मेरे अध्ययन के परिणाम बताते हैं कि अधिकांश कोड प्रावधान तापमान 15°C से नीचे होने पर स्ट्रिपिंग समय के बारे में विशिष्ट दिशा-निर्देश नहीं प्रदान करते हैं। कुछ कोड क्षेत्र परीक्षण और गैर-विनाशकारी परीक्षण (NDTs) की सिफारिश करते हैं ताकि

यह सुनिश्चित किया जा सके कि मानकों में इंगित मापदंडों से विचलन होने पर स्ट्रिपिंग के लिए आवश्यक अवधि का निर्धारण किया जा सके। आमतौर पर, झुकने वाले संरचनात्मक तत्वों के लिए, यह सलाह दी जाती है कि जब ताजा ढाला गया कंक्रीट लक्षित शक्ति का 70% या उससे अधिक संपीड़न शक्ति प्राप्त कर ले, तो नीचे का फार्मवर्क हटा दिया जाए। विभिन्न कंक्रीट घटकों के फार्मवर्क हटाने की अवधि, विभिन्न राष्ट्रों में अभ्यास किए गए कोडों में उल्लिखित, बारह घंटे से अट्हाईस दिनों तक होती है। फिर भी, कुछ विनियमों ने साइट पर कंक्रीट की संपीड़न शक्ति के आधार पर फार्मवर्क हटाने की अवधि निर्दिष्ट की है, जो 3.5 MPa से 14 MPa (N/mm²) तक होती है।

लेखक द्वारा किए गए प्रयोगों के आधार पर, लंबवत कंक्रीट संरचनाओं के फार्मवर्क को हटाने के लिए 6 घंटे से 5.5 दिनों के भीतर एक समय सीमा आवश्यक है। विशिष्ट अवधि प्रयुक्त सीमेंट के प्रकार और तापमान सीमा पर निर्भर करती है, जो 0°C से 45°C तक हो सकती है। क्षैतिज फार्मवर्क हटाने की अवधि 2.6 से 124.4 दिनों तक भिन्न होती है, जो सीमेंट ग्रेड और परिवेश तापमान सीमा 45°C से 0°C पर निर्भर करती है। फार्मवर्क हटाने के समय अत्यधिक तनाव और संभावित क्षति से बचने के लिए सावधानी बरतना महत्वपूर्ण है, विशेष रूप से जब परिवेश तापमान 15°C से नीचे हो। यह कई मानक अभ्यास कोडों में उचित अवधि के लिए दिशा-निर्देशों की कमी के कारण है जब तापमान 15°C से नीचे हो। आईआईटी दिल्ली में किए गए इस अध्ययन के प्रयोगशाला निष्कर्षों के आधार पर, यह अनुशंसा की जाती है कि नाममात्र मिश्रण सीमेंट कंक्रीट को सामान्य पोर्टलैंड सीमेंट (OPC) के साथ बनाए गए कंक्रीट में लंबवत फार्मवर्क को सुरक्षित रूप से हटाने के लिए 3.50 MPa से अधिक संपीड़न शक्ति होनी चाहिए। पोर्टलैंड पोर्जोलाना सीमेंट (PPC) का उपयोग करके बनाए गए कंक्रीट के लिए, संपीड़न शक्ति कम से कम 3.25 MPa होनी चाहिए। फिर भी, सामग्री गुणों, पर्यावरणीय परिस्थितियों, और निर्माण तकनीकों में भिन्नताओं का स्ट्रिपिंग प्रक्रिया के समय पर प्रभाव हो सकता है।

यह अध्ययन गैर-विनाशकारी परीक्षण तकनीकों की जांच करता है ताकि फार्मवर्क हटाने के इष्टतम समय का निर्धारण किया जा सके बिना कंक्रीट संरचना को नुकसान पहुंचाए। यह शोध रिबाउंड हथौड़ा और अल्ट्रासोनिक पल्स वेग (UPV) मापन तकनीक का उपयोग करता है। लचीले सदस्यों के मामले में, जब तक कठोर कंक्रीट कम से कम 70 प्रतिशत संपीड़न शक्ति प्राप्त नहीं कर लेता, तब तक नीचे का फार्मवर्क नहीं हटाना चाहिए। लंबवत कंक्रीट तत्वों के लिए न्यूनतम 3.5 MPa शक्ति की आवश्यकता होती है ताकि कंक्रीट की छीलन को रोका जा सके। इन मानदंडों के आधार पर, यह अध्ययन सुझाव देता है कि फार्मवर्क को तब हटाया जाना चाहिए जब रिबाउंड संख्या (RN) 3.0 इकाइयों से अधिक हो और लंबवत घटकों के लिए अल्ट्रासोनिक पल्स वेग (UPV) 2.6 किमी/सेकंड से अधिक हो। लचीले कंक्रीट तत्वों के लिए, यह सलाह दी जाती है कि RN और UPV मान 15.0 इकाइयों और 3.0 किमी/सेकंड से अधिक हों, क्रमशः। प्रस्तावित तकनीक विभिन्न वायुमंडलीय स्थितियों और कंक्रीट की चर रचनाओं को ध्यान में रखते हुए फार्मवर्क को हटाने के समय का अधिक विश्वसनीय और सटीक तरीका प्रदान करती है। RCC निर्माण में इष्टतम दक्षता तब प्राप्त की जाती है जब फार्मवर्क को जितनी जल्दी हो सके हटा दिया जाए, जबकि यह सुनिश्चित करते हुए कि कंक्रीट को कोई नुकसान नहीं हुआ हो।

यह अध्ययन ठंडे परिवेश तापमान (15°C से नीचे) में प्रबलित कंक्रीट संरचनाओं से फार्मवर्क हटाने के लिए आवश्यक समय को कम करने के लिए ताजा कंक्रीट मिश्रण में सुपरप्लास्टिसाइज़र और नैनोमटेरियल्स की प्रभावकारिता का आकलन करने का उद्देश्य रखता है। प्रयोगात्मक जांच के अनुसार, 0.5% सुपरप्लास्टिसाइज़र को 1% नैनो-कोलॉइडल सिलिका (NCS) के साथ मिलाने से स्ट्रिपिंग के लिए आवश्यक समय को प्रभावी ढंग से कम किया जा सकता है, जिससे फार्मवर्क खर्चों में कमी आती है। यह प्रभाव तब भी बना रहता है जब परिवेश का तापमान 15°C से नीचे हो। लंबवत फार्मवर्क फार्मवर्क स्ट्रिपिंग के लिए आवश्यक समय को काफी हद तक कम कर देता है, इसे 0-5°C

तापमान सीमा के भीतर 4.5 दिनों से घटाकर केवल एक दिन कर देता है। हालांकि, स्लैब फार्मवर्क को हटाने के लिए आवश्यक समय 0°C पर 54 से 37 दिनों तक कम हो जाता है। लागत विश्लेषण से पता चलता है कि 0.5% सुपरप्लास्टिसाइज़र और 1% NCS को कंक्रीट में शामिल करके, फार्मवर्क खर्चों में कमी के कारण कुल RCC की लागत को कम किया जा सकता है।

यह अध्ययन विनाशकारी और गैर-विनाशकारी परीक्षणों का उपयोग करके लंबवत और क्षैतिज कंक्रीट तत्वों से फार्मवर्क हटाने के लिए संपीड़न शक्ति और निष्कर्षण समय का पता लगाने के लिए कंक्रीट प्रयोगशाला में किए गए प्रयोगों के प्रारंभिक परिणाम प्रस्तुत करता है। अनुसंधान विभिन्न तापमानों पर प्रबलित सीमेंट कंक्रीट से बने सदस्यों के लिए फार्मवर्क स्ट्रिपिंग समय का निर्धारण करता है। इस जानकारी का उपयोग विभिन्न तापमानों पर किए गए RCC कार्यों में प्रैक्टिशनर्स द्वारा किया जा सकता है, विशेष रूप से जब तापमान 15°C से नीचे हो।

कुंजी शब्द: एडमिक्सचर्स, परिवेश का तापमान, सीमेंट, कंक्रीट, लागत विश्लेषण, विनाशकारी परीक्षण (DT), क्षैतिज और लंबवत फार्मवर्क, कंक्रीट की परिपक्वता, नैनोमटेरियल्स, गैर-विनाशकारी परीक्षण (NDT), रिबाउंड हथौड़ा (RH), स्ट्रिपिंग अवधि, सुपरप्लास्टिसाइज़र, अल्ट्रासोनिक पल्स वेग (UPV)

CONTENTS

CERTIFICATE	i
ACKNOWLEDGEMENTS	ii
ABSTRACT.....	iv
सारांश	viii
CONTENTS	xii
LIST OF FIGURES	xx
LIST OF TABLES.....	xxiv
LIST OF ABBREVIATION	xxvi
CHAPTER 1 INTRODUCTION	1
1.1 Background	1
1.2 Research Gaps and Motivation.....	5
1.3 Research Questions	7
1.4 Research Objectives.....	7
1.5 Research Methodology	8
1.6 Organization of the Thesis	9
1.7 Summary.....	10
CHAPTER 2 CONCRETING AND FORMWORK -TRADITIONAL PRACTICES IN RURAL AND SEMI-URBAN AREAS	13
2.1 Introduction.....	13

2.2	Formwork Practices	13
2.3	Concreting Practices	22
2.3.1	Mixing of ingredients of concrete	22
2.3.2	Pouring of fresh concrete	25
2.3.3	Curing of hardened concrete	28
2.4	Summary	31
CHAPTER 3 LITERATURE REVIEW		33
3.1	Background	33
3.2	Types of Formworks	34
3.3	Factors Affecting Formwork Removal Time	35
3.3.1	Effect of ambient temperature on stripping time	37
3.3.2	Use of nanoparticles in concrete mix	40
3.3.3	Role of admixtures in concrete	46
3.3.4	Effect of curing on concrete	50
3.3.5	Type and grade of concrete	52
3.4	Tests to Find the Strength of Concrete	53
3.4.1	Non-Destructive test for concrete	54
3.4.2	Destructive test for concrete (Compression Test)	59
3.5	Concrete Maturity Concept	61
3.5.1	Use of maturity method in formwork planning in construction	63
3.6	Removal of Formwork	66

3.7	Concluding Remarks and Research Gaps	67
CHAPTER 4 RESEARCH METHODOLOGY		71
4.1	Introduction	71
4.2	General Experimental Set-up for Determination of Research Objectives .	71
4.3	Methodology for Research Objective -1	73
4.4	Methodology for Research Objective -2	75
4.4.1	Stripping time estimation for vertical concrete members	76
4.4.2	Stripping time estimation of horizontal concrete members	76
4.5	Methodology for Research Objective -3	78
4.6	Methodology for Research Objective -4	79
4.7	Methodology for Research Objective -5	80
4.7.1	Mix proportions	80
4.7.2	Calculation of stripping time for vertical formwork.....	81
4.7.3	Calculation of stripping time for horizontal formwork	82
4.8	Summary	82
CHAPTER 5 COMPARISON OF STRIPPING -TIMES OF FORMWORK FOR REINFORCED CEMENT CONCRETE STRUCTURES		83
5.1	Introduction	83
5.2	The Standard Norms for Formwork Stripping Periods in Different Countries	84
5.3	Indian Standard Recommendations (IS 456:2000)	84
5.4	Japanese Standard Recommendations (JSCE-16)	86

5.5	British Standard Recommendations (BS 8110-1:1997 and reaffirmed in 2007)	87
5.6	American Standard Recommendations [ACI 347-04 and reaffirmed in ACI 347R-14(2014)]	89
5.7	German Standard Recommendations (DIN 1045-3)	92
5.8	Ugandan Code Recommendations (Standard Specifications for Building Works Part 1 - Section 4)	95
5.9	ASTM C-1074-19 Recommendation	96
5.10	Discussion	97
5.11	Concluding Remarks	99
	CHAPTER 6 EXPERIMENTAL INVESTIGATIONS AND THE OUTCOME OF FORMWORK STRIPPING-TIME FOR NOMINAL MIX CONCRETE	103
6.1	Background	103
6.2	Overview of Experimental Specimen Preparation and Testing	104
6.2.1	Description of material components and composition of concrete	105
6.2.2	Preparation of specimens	107
6.2.3	Testing of specimen	107
6.2.4	Test results	108
6.3	Determination of Formwork Removal Time	112
6.3.1	Vertical concrete members	112
6.3.2	Horizontal concrete members	113
6.4	Discussion	122

6.5	Concluding Remarks	126
CHAPTER 7 EXPERIMENTAL INVESTIGATIONS AND THE OUTCOME OF FORMWORK STRIPPING-TIME FOR DESIGN MIX CONCRETE		129
7.1	Introduction	129
7.2	Overview of Experimental Specimen Preparation and Testing	129
7.3	Experimental Set-up	130
7.3.1	Test results for vertical members	131
7.3.2	Test results for horizontal members	131
7.4	Determination of Formwork Removal Time	137
7.4.1	Vertical concrete members	137
7.4.2	Horizontal concrete members	138
7.5	Discussion	146
7.6	Summary and Conclusions	148
CHAPTER 8 DETERMINATION OF STRIPPING TIME OF FORMWORK FOR CONCRETE MEMBERS USING NON-DESTRUCTIVE TEST METHODS		151
8.1	Introduction	151
8.2	Visual Inspection Method	153
8.3	Ultrasonic Pulse Velocity Test	154
8.4	Rebound Hammer Test	155
8.5	Experimental Preparation and Testing of Specimen	157
8.5.1	Description of ingredients and composition of concrete	157
8.5.2	Preparation of specimens	158

8.5.3	Testing of specimens	159
8.6	Calibration of the Testing Devices	159
8.7	Calculation of Formwork Stripping Time Based on Calibration Curves.	163
8.7.1	Calculation of stripping time for vertical members	163
8.7.2	Calculation of stripping time for horizontal members	164
8.8	Conclusions and Recommendations	165
CHAPTER 9 ECONOMIC EFFECTIVENESS OF REDUCING THE STRIPPING		
TIME FOR FORMWORK USING NANOMATERIALS AND		
SUPERPLASTICIZERS		
169		
9.1	Introduction	169
9.2	Experimental Procedures	170
9.2.1	Mix Proportions	170
9.2.2	Testing	172
9.3	Calculation of Stripping Time	172
9.3.1	Calculation of stripping time for vertical formwork	172
9.3.2	Calculation of stripping time for horizontal formwork	174
9.4	Results and Discussion	179
9.5	Cost Analysis of Formwork	181
9.6	Summary and Conclusions	187
CHAPTER 10 SUMMARY AND CONCLUSIONS		
189		
10.1	Introduction	189
10.2	Summary of the Study	189

10.3	Conclusions and Recommendations	194
10.4	Contributions of the Study	198
10.5	Limitations of the Study	200
10.6	Scope for Future Research Work	200
	REFERENCES	203
	APPENDIX A	227
	APPENDIX B	231
	APPENDIX C	233
	APPENDIX D	237
	LIST OF PUBLICATIONS BASED ON THESIS	239
	BIODATA OF THE AUTHOR	241

LIST OF FIGURES

Figure 2.1: Locally available bamboo used in formwork activities	14
Figure 2.2: Use of locally available wooden props and wooden deck in formwork	15
Figure 2.3: Use of bamboo props and wooden deck in formwork	15
Figure 2.4: Staircase support through bamboo props.	16
Figure 2.5: Typical formwork support for concrete water tanks in rural areas	16
Figure 2.6: Wooden planks as formwork to support the slab	17
Figure 2.7: Bamboo props as formwork to support beams	17
Figure 2.8: Brickwork used as formwork for beams	18
Figure 2.9: Column formwork supported by brick walls	18
Figure 2.10: Formwork practices for slab and beam in a semi-urban area at a construction site..	19
Figure 2.11: Formwork practices for slab and beam in a semi-urban area in row-housing	20
Figure 2.12: Wooden formwork for a wall in a rural area	20
Figure 2.13: Wooden formwork for a wall in a semi-urban area	21
Figure 2.14: Formwork practices for column and footing in a semi-urban area	21
Figure 2.15: Formwork practices for column and footing in a semi-urban area	22
Figure 2.16: Locally available aggregates	23
Figure 2.17: Cement bags carried manually by labor	23
Figure 2.18: All ingredients stacked in one space	24
Figure 2.19: Batching of aggregates	24
Figure 2.20: Manual mixing of water to other ingredients of concrete	25
Figure 2.21: Manual mixing for making fresh concrete.....	25
Figure 2.22: Concrete drum mixer	25
Figure 2.23: Concrete carried manually in rural areas	26
Figure 2.24: Newly mixed fresh concrete.....	26

Figure 2.25: Pouring of newly mixed fresh concrete.....	27
Figure 2.26: Pouring, distribution, and leveling of concrete in rural areas	27
Figure 2.27: Curing of concrete by water pounding on the slab.....	29
Figure 2.28: Curing of concrete by water pounding.....	29
Figure 2.29: Concrete pouring, spreading, and leveling in semi-urban areas	30
Figure 2.30: Concreting in semi-urban areas on the inclined roof slab	30
Figure 3.1: Types of formwork used in concrete constructions (Li et al. 2022).....	35
Figure 3.2: Variation of ultimate strain by previous models and proposed model (El-Zohairy et al. 2020)	39
Figure 3.3: Effect of temperature on high performance concrete (HPC) and ultra-high performance concrete (UHPC) (Deutscher et al. 2022)	40
Figure 3.4: Particle size of nanomaterials used in concrete (Sobolev and Gutiérrez, 2005)	41
Figure 3.5: (a) Specimen for Schmidt rebound hammer test, (b) Setup of Schmidt rebound hammer test, (c) Schmidt rebound hammer equipment, and (d) sample of Schmidt rebound hammer test (Laurens et al., 2005)	56
Figure 3.6: Setup for compression testing	60
Figure 3.7: Maturity of concrete concerning datum temperature	62
Figure 3.8: Formwork removal process	67
Figure 4.1: Research methodology for the objectives.....	74
Figure 6.1: Concrete's compressive strength (with OPC 43) versus time (in days) for curing ...	115
Figure 6.2: Concrete's compressive strength (with PPC 53) versus time (in days) curing at 27°C, the graph denotes best-fit data	115
Figure 6.3: Evaluation of the limiting strength using a plot of reciprocal strength versus reciprocal age (for concrete with OPC 43)	116
Figure 6.4: Evaluation of the limiting strength using a plot of reciprocal strength versus reciprocal age (for concrete with PPC 53).....	117

Figure 6.5: Determining the rate constant and the age at which strength development starts (for concrete with OPC 43)	118
Figure 6.6: Determining the rate constant and the age at which strength development starts (for concrete with PPC 53).....	118
Figure 6.7: Relative strength of concrete versus equivalent age at 27°C (for concrete with OPC 43).....	119
Figure 6.8: Relative strength of concrete versus equivalent age at 27°C (for concrete with PPC 53)	120
Figure 7.1:(a) to (f) Showing Concrete production, casting, curing, stripping time estimation, and testing design mix concrete specimens for vertical and horizontal concrete members	134
Figure 7.2: Concrete’s compressive strength (with OPC 43) versus time (in days) for curing...	140
Figure 7.3: Concrete’s compressive strength (with PPC 53) versus time (in days) curing	140
Figure 7.4: Evaluation of the limiting strength using a plot of reciprocal strength versus reciprocal age (for concrete with OPC 43)	141
Figure 7.5: Evaluation of the limiting strength using a plot of reciprocal strength versus reciprocal age (for concrete with PPC 53).....	141
Figure 7.6: Determining the rate constant and the age at which strength development starts (for concrete with OPC 43)	142
Figure 7.7: Determining the rate constant and the age at which strength development starts (for concrete with PPC 53).....	142
Figure 7.8: Relative strength of concrete versus equivalent age at 27°C (for concrete with OPC 43).....	143
Figure 7.9: Relative strength of concrete versus equivalent age at 27°C (for concrete with PPC 53)	144
Figure 8.1: Ultrasonic pulse velocity test through 15 cm concrete specimen.....	155
Figure 8.2: Rebound hammer test on 15 cm concrete specimen	156

Figure 8.3: Rebound hammer impact on concrete surfaces after rebound hammer test on concrete samples	156
Figure 8.4: Determining rebound number (RN) value and ultimate crushing load on CTM	159
Figure 8.5: Calibration curve for ultrasonic pulse velocity vs. the compressive strength.....	161
Figure 8.6: Calibration curve for Rebound number values versus the compressive strength.....	162
Figure 8.7: Calibration curve for the experimentally obtained compressive strength vs. manufacturer-provided values	162
Figure 9.1: Casting of concrete cubes for Group 1 and Group 2 in the laboratory	171
Figure 9.2: Compressive strength vs. curing age at 27°C	176
Figure 9.3: Plot of reciprocal strength vs. reciprocal age	176
Figure 9.4: Plot to evaluate the rate constant and the age when strength development begins ..	177
Figure 9.5: Relative strength vs. equivalent age at 27°C	178
Figure 9.6: Stripping time of formwork at various temperatures for vertical members - Column	180
Figure 9.7: Stripping time of formwork at various temperatures for horizontal members - Slab	180
Figure 9.8: Stripping time of formwork at various temperatures for horizontal members – Beam	181
Figure 9.9: Cost analysis of vertical member - Column.....	183
Figure 9.10: Cost reduction of formwork at different temperatures for vertical member – Column	184
Figure 9.11: Cost analysis of horizontal member - Slab	185
Figure 9.12: Cost reduction of formwork at different temperatures for horizontal member – Slab	185
Figure 9.13: Cost analysis of horizontal member - Beam	186
Figure 9.14: Cost reduction of formwork at different temperatures for horizontal member – Beam	186

LIST OF TABLES

Table 3.1: Stripping of formwork for different structural members corresponding to their strength gain.....	36
Table 3.2: Formwork stripping time for different parts of concrete buildings	52
Table 3.3: Formulations of cubic strength (R_{cub}) and cylindrical strength (f_{cyl}) with rebound index(I_r) and ultrasound velocity (V_{us}) (Cristofaro et al., 2020).....	57
Table 4.1: Ingredients of concrete per cubic m of cement concrete mix.....	81
Table 5.1: Formwork removal time for different RCC elements by Indian Standards (Source: IS 456:2000. Bureau of Indian Standards).....	85
Table 5.2: The Japanese requirement of compressive strength of concrete just before removing formwork (Source: Japan Society of Civil Engineers (JSCE), Standard Specifications for Concrete Structures - 2007 “Materials and Construction).....	86
Table 5.3: Minimum stripping time for formwork (British) (Source: British Standard (BS 8110-1:1997), Structural use of concrete —Part 1: Code of practice for design and construction. 1997)	88
Table 5.4: American guidelines for formwork stripping time (Source ACI 347-14).....	90
Table 5.5: Minimum duration of post-treatment of concrete for the exposure classes (Source: DIN 1045-2) (German).....	93
Table 5.6: Minimum duration of post-treatment of concrete for exposure classes XC2, XC3, XC4, and XF1. Source: DIN 1045-2 (German)	94
Table 5.7: Minimum times for striking formwork (Uganda) (Source: Standard Specifications Building for Works. Ministry of Works and Transport. Government of Uganda. 2013)	95
Table 6.1: Mix ingredients for the two grades of concrete mixes	106
Table 6.2: Compressive strengths at different temperatures for concrete made with OPC and PPC	110
Table 6.3: Calculation of average compressive strength concrete cured at 27°C	111

Table 6.4: Recommended time and compressive strength reference values for removing vertical formwork.....	114
Table 6.5: Age conversion factor and amount of time required for the removal of beam and slab horizontal formwork	121
Table 7.1: Design mix ingredients for the two grades of concrete mixes	130
Table 7.2: Compressive strengths at different temperatures for Design mix concrete made with OPC and PPC.....	135
Table 7.3: Calculation of average compressive strength of design mix concrete cured at 27°C.	136
Table 7.4: Recommended time and compressive strength reference values for removing vertical formwork.....	138
Table 7.5: Age conversion factor and amount of time required for the removal of beam and slab horizontal formwork	145
Table 8.1: Velocity criteria for the concrete quality grading (IS 13311 (Part 1) 1992)	154
Table 8.2: Ingredients for 1 m ³ of cement concrete mix for the nominal mix	158
Table 8.3: Ingredients for 1 m ³ of cement concrete mix for the design mix.....	158
Table 8.4: Ultrasonic pulse velocity (UPV), rebound number (RN) value, crushing strength, and compressive strength (MPa) for the nominal and design mixes on 15 cm concrete cube specimens	160
Table 8.5: Calculation of stripping time for vertical members at temperatures 15 to 20 °C	164
Table 8.6: Rebound Number values and UPV data for horizontal concrete members	165
Table 9.1: Ingredients of concrete per cubic m of cement concrete mix.....	171
Table 9.2: Stripping time and compressive strength of vertical members for Group 1 and Group 2	173
Table 9.3: Compressive strength of Group 1 and Group 2 at 27 °C.....	175
Table 9.4: Stripping time of horizontal members (Slab and Beam) for Group 1 and Group 2 ...	179

LIST OF ABBREVIATION

ACI	American Concrete Institute
ASTM	American Society for Testing and Materials
BIS	Bureau of Indian Standards
BS	British Standard
C-S-H	Calcium-Silicate-Hydrate
CTM	Compression Testing Machine
DIN	Deutsches Institut für Normung (German code)
DT	Destructive Test
HAC	High Alumina Cement
HESPC	High Early Strength Portland Cement
HPC	High-Performance Concrete
IS	Indian Standard
JSCE	Japan Society of Civil Engineers
MC	Material Criticality
MPA	Mega Pascal
NDT	Non-Destructive Test
OPC	Ordinary Portland Cement
PCC	Plain Cement Concrete
PPC	Portland Pozzolana Cement
QA	Quality Assurance
QC	Quality Control
QSC	Quick Setting Cement

RCC	Reinforced Cement Concrete
RHV	Rebound Hammer Value
RPC	Rapid Hardening Cement
SCM	Supplemental Cementitious Materials
SCC	Self-Compacting Concrete
SH	Schmidt Hammer
SP	Special Publication
UPV	Ultrasonic Pulse Velocity